

# 300-710<sup>Q&As</sup>

Securing Networks with Cisco Firepower (SNCF)

**Pass Cisco 300-710 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/300-710.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

Which group within Cisco does the Threat Response team use for threat analysis and research?

- A. Cisco Deep Analytics
- B. OpenDNS Group
- C. Cisco Network Response
- D. Cisco Talos

Correct Answer: D

Reference: <https://www.cisco.com/c/en/us/products/security/threat-response.html#~benefits>

---

### QUESTION 2

An engineer is configuring Cisco FMC and wants to allow multiple physical interfaces to be part of the same VLAN. The managed devices must be able to perform Layer 2 switching between interfaces, including sub-interfaces. What must be configured to meet these requirements?

- A. inter-chassis clustering VLAN
- B. Cisco ISE Security Group Tag
- C. interface-based VLAN switching
- D. integrated routing and bridging

Correct Answer: C

---

### QUESTION 3

After using Firepower for some time and learning about how it interacts with the network, an administrator is trying to correlate malicious activity with a user. Which widget should be configured to provide visibility on the Cisco Firepower Dashboards?

- A. Custom analysis.
- B. Current Status
- C. Current Sessions
- D. Correlation Events

Correct Answer: A

---

#### QUESTION 4

An organization is using a Cisco FTD and Cisco ISE to perform identity-based access controls. A network administrator is analyzing the Cisco FTD events and notices that unknown user traffic is being allowed through the firewall. How should this be addressed to block the traffic while allowing legitimate user traffic?

- A. Modify the Cisco ISE authorization policy to deny this access to the user.
- B. Modify Cisco ISE to send only legitimate usernames to the Cisco FTD.
- C. Add the unknown user in the Access Control Policy in Cisco FTD.
- D. Add the unknown user in the Malware and File Policy in Cisco FTD.

Correct Answer: C

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/640/fdm/fptd-fdm-config-guide-640/fptd-fdm-identity.html#concept\\_655B055575E04CA49B10186DEBDA301A](https://www.cisco.com/c/en/us/td/docs/security/firepower/640/fdm/fptd-fdm-config-guide-640/fptd-fdm-identity.html#concept_655B055575E04CA49B10186DEBDA301A)

---

#### QUESTION 5

A network security engineer must replace a faulty Cisco FTD device in a high availability pair. Which action must be taken while replacing the faulty unit?

- A. Ensure that the faulty Cisco FTD device remains registered to the Cisco FMC
- B. Shut down the active Cisco FTD device before powering up the replacement unit
- C. Shut down the Cisco FMC before powering up the replacement unit
- D. Unregister the faulty Cisco FTD device from the Cisco FMC

Correct Answer: A

---

#### QUESTION 6

An analyst is reviewing the Cisco FMC reports for the week. They notice that some peer-to-peer applications are being used on the network and they must identify which poses the greatest risk to the environment. Which report gives the analyst this information?

- A. Attacks Risk Report
- B. User Risk Report
- C. Network Risk Report
- D. Advanced Malware Risk Report

Correct Answer: C

---

### QUESTION 7

What is a result of enabling Cisco FTD clustering?

- A. For the dynamic routing feature, if the master unit fails, the newly elected master unit maintains all existing connections.
- B. Integrated Routing and Bridging is supported on the master unit.
- C. Site-to-site VPN functionality is limited to the master unit, and all VPN connections are dropped if the master unit fails.
- D. All Firepower appliances can support Cisco FTD clustering.

Correct Answer: C

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/clustering\\_for\\_the\\_firepower\\_threat\\_defense.html](https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/clustering_for_the_firepower_threat_defense.html)

---

### QUESTION 8

Which command is run on an FTD unit to associate the unit to an FMC manager that is at IP address 10.0.0.10, and that has the registration key Cisco123?

- A. configure manager local 10.0.0.10 Cisco123
- B. configure manager add Cisco123 10.0.0.10
- C. configure manager local Cisco123 10.0.0.10
- D. configure manager add 10.0.0.10 Cisco123

Correct Answer: D

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/misc/fmc-ftd-mgmt-nw/fmc-ftd-mgmt-nw.html#id\\_106101](https://www.cisco.com/c/en/us/td/docs/security/firepower/misc/fmc-ftd-mgmt-nw/fmc-ftd-mgmt-nw.html#id_106101)

---

### QUESTION 9

A network administrator is seeing an unknown verdict for a file detected by Cisco FTD. Which malware policy configuration option must be selected in order to further analyze the file in the Talos cloud?

- A. malware analysis
- B. dynamic analysis
- C. sandbox analysis
- D. Spero analysis

Correct Answer: A

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/60/configuration/guide/fpmc-config-guide-v60/Reference\\_a\\_wrapper\\_Chapter\\_topic\\_here.html](https://www.cisco.com/c/en/us/td/docs/security/firepower/60/configuration/guide/fpmc-config-guide-v60/Reference_a_wrapper_Chapter_topic_here.html)

---

#### QUESTION 10

Which two conditions must be met to enable high availability between two Cisco FTD devices? (Choose two.)

- A. same flash memory size
- B. same NTP configuration
- C. same DHCP/PPoE configuration
- D. same host name
- E. same number of interfaces

Correct Answer: BE

---

#### QUESTION 11

An engineer must investigate a connectivity issue and decides to use the packet capture feature on Cisco FTD. The goal is to see the real packet going through the Cisco FTD device and see Snort detection actions as a part of the output. After the capture-traffic command is issued, only the packets are displayed. Which action resolves this issue?

- A. Specify the trace using the -T option after the capture-traffic command
- B. Perform the trace within the Cisco FMC GUI instead of the Cisco FMC CLI
- C. Use the verbose option as a part of the capture-traffic command
- D. Use the capture command and specify the trace option to get the required information

Correct Answer: C

---

#### QUESTION 12

An organization has seen a lot of traffic congestion on their links going out to the internet. There is a Cisco Firepower device that processes all of the traffic going to the internet prior to leaving the enterprise. How is the congestion alleviated so that legitimate business traffic reaches the destination?

- A. Create a NAT policy so that the Cisco Firepower device does not have to translate as many addresses.
- B. Create a flexconfig policy to use WCCP for application aware bandwidth limiting.
- C. Create a QoS policy rate-limiting high bandwidth applications.
- D. Create a VPN policy so that direct tunnels are established to the business applications.

Correct Answer: C

---

### QUESTION 13

In which two ways do access control policies operate on a Cisco Firepower system? (Choose two.)

- A. Traffic inspection is interrupted temporarily when configuration changes are deployed.
- B. The system performs intrusion inspection followed by file inspection.
- C. They block traffic based on Security Intelligence data.
- D. File policies use an associated variable set to perform intrusion prevention.
- E. The system performs a preliminary inspection on trusted traffic to validate that it matches the trusted parameters.

Correct Answer: AC

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/60/configuration/guide/fpmc-config-guide-v60/Access\\_Control\\_Using\\_Intrusion\\_and\\_File\\_Policies.html](https://www.cisco.com/c/en/us/td/docs/security/firepower/60/configuration/guide/fpmc-config-guide-v60/Access_Control_Using_Intrusion_and_File_Policies.html)

---

### QUESTION 14

A network engineer is extending a user segment through an FTD device for traffic inspection without creating another IP subnet. How is this accomplished on an FTD device in routed mode?

- A. by assigning an inline set interface
- B. by using a BVI and creating a BVI IP address in the same subnet as the user segment
- C. by leveraging the ARP to direct traffic through the firewall
- D. by bypassing protocol inspection by leveraging pre-filter rules

Correct Answer: B

[https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/transparent\\_or\\_routed\\_firewall\\_mode\\_for\\_firepower\\_threat\\_defense.html](https://www.cisco.com/c/en/us/td/docs/security/firepower/640/configuration/guide/fpmc-config-guide-v64/transparent_or_routed_firewall_mode_for_firepower_threat_defense.html)

---

### QUESTION 15

Which Cisco Firepower Threat Defense, which two interface settings are required when configuring a routed interface? (Choose two.)

- A. Redundant Interface
- B. EtherChannel
- C. Speed
- D. Media Type

E. Duplex

Correct Answer: CE

<https://www.cisco.com/c/en/us/td/docs/security/firepower/610/fdm/fptd-fdm-config-guide-610/fptd-fdm-interfaces.html>

[300-710 Practice Test](#)

[300-710 Study Guide](#)

[300-710 Braindumps](#)

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

## Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.certbus.com/allproducts>

## Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p><b>One Year Free Update</b> Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p><b>Money Back Guarantee</b> To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p><b>Security &amp; Privacy</b> We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information &amp; peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © certbus, All Rights Reserved.