

100% Money Back
Guarantee

Vendor: EMC

Exam Code: E20-405

Exam Name: EMC Content Management Server
Programming(CMSP)

Version: Demo

QUESTION 1

Which statement is true about the object model?

- A. dmr_content is not a sub-type of dm_sysobject although sysobject contents are stored as dmr_content objects.
- B. dm_acl objects are stored in the System cabinet.
- C. Not all sysobjects can have associated permissions.
- D. Virtual documents are objects of type dm_relation that describe a parent/child relationship between objects.

Correct Answer: A

QUESTION 2

How do you manually configure the DFC global registry?

- A. 1. add the dfc.bof.registry entries to the dfc.properties file.
- B. 1. encrypt the password2. add the dfc.bof.registry entries to the dfc.properties file.
- C. 1. activate the registry user2. change the password3. encrypt the password4. add the dfc.bof.registry entries to the dfc.properties file.
- D. 1. create a new user as a consumer2. designate the user as a registry user3. encrypt the password4. add the dfc.bof.registry entries to the dfc.properties file.

Correct Answer: C

QUESTION 3

You have a working registered table called "CompanyList" with one string column called "CompanyName" with one row value "EMC." What is the output of the following statements?

- A. null
- B. EMC
- C. CompanyName
- D. A DfException is thrown.

Correct Answer: D

QUESTION 4

Which statement is true?

- A. You use the IDfClient.getQuery method to obtain an IDfQuery object.
- B. The execute method of an IDfQuery object returns an IDfCollection.
- C. The execute method of an IDfQuery object returns an IDfEnumeration.
- D. The execute method of an IDfQuery object only requires the repository name as a parameter.

Correct Answer: B

QUESTION 5

Which code should you use to create a copy of the current object and place it in CopyCab?

- A. IDfSysObject sysObj = (IDfSysObject)session.getObject(myId);sysObj.link("/CopyCab");sysObj.savelock();
- B. IDfSysObject sysObj = (IDfSysObject)session.getObject(myId);sysObj.unlink("/SourceCab");sysObj.link("/CopyCab");sysObj.saveAsNew(false);
- C. IDfSysObject sysObj = (IDfSysObject)session.newObject(myId);sysObj.link("/CopyCab");sysObj.save();
- D. IDfSysObject sysObj =

```
(IDfSysObject)session.getObject(myId);sysObj.unlink("/SourceCab");sysObj.link("/CopyCab");sysObj.save();
```

Correct Answer: B

QUESTION 6

When are the binding rules for a virtual document actually applied?

- A. When the virtual document is saved
- B. When IDfSysObject.asVirtualDocument() is called
- C. When IDfVirtualDocumentNode.getChildCount() is called
- D. When IDfVirtualDocument.getRootNode() is called

Correct Answer: C

QUESTION 7

Which statement is true?

- A. IDfSession.getLoginTicket() will return a ticket from the current session.
- B. IDfSession.getLoginTicket() will return a new session object for the current user.
- C. IDfSession.getLoginTicket() will return a new session object for the super user.
- D. IDfSession.getLoginTicket() will return a ticket from a new session.

Correct Answer: A

QUESTION 8

Which DFC interface provides a getCheckoutDirectory() method that returns the local checkout directory?

- A. IDfClient
- B. IDfClientX
- C. IDfSession
- D. IDfClientRegistry

Correct Answer: D

QUESTION 9

Which statement is true about Trusted Content Services (TCS)?

- A. TCS is not required to create ApplicationPermission entries.
- B. TCS is not required to evaluate ApplicationPermission entries.
- C. TCS is not required to delete ApplicationPermission entries.
- D. TCS validates and enforces application permissions at the server level.

Correct Answer: B

QUESTION 10

Where are the credentials located for the BOF's client dynamic delivery mechanism?

- A. dfc.properties
- B. dmcl.ini
- C. bof.properties
- D. dbor.properties

Correct Answer: A

QUESTION 11

Which SBO method signature is valid for conversion to a web service?

- A. void setKeyword(IDfSysObject obj, int index, String value)
- B. boolean uploadConfiguration(java.io.File myFile)
- C. boolean setKeyword(IDfSysObject obj, int index, String value)
- D. int countDocuments(IDfSession sess, String qualification)

Correct Answer: B

QUESTION 12

What happens when you fail to close open query collections in a DFC application?

- A. Performance for other users will be impaired.
- B. Eventually, no more queries can be executed.
- C. Garbage collection will release appropriate resources.
- D. The session will disconnect.

Correct Answer: B

QUESTION 13

What kind of module is used to create a Documentum Web Service?

- A. Type-based Business Object
- B. Service-based Business Object
- C. Web-based Business Object
- D. Custom Module

Correct Answer: B

QUESTION 14

Given the following repositories that are projecting to the following Connection Brokers:
How do you dynamically add host2 as additional Connection Broker, such that Docbase A and Docbase B are listed as available repositories?

- A. change "host = host1" to "host = host1, host2" in dmcl.ini
- B. execute IDfDocbrokerClient.addDocbroker("host2",1489);
- C. add the following statements in the dmcl.ini:[DOCBROKER_BACKUP_1] host=host2 port=1489
- D. add the following statements in the dmcl.ini:[DOCBROKER_SECONDARY] host=host2 port=1489

Correct Answer: B

QUESTION 15

Given the following architecture: To disable full-text search for end users of Webtop, on which computer should you update the dfc.properties file?

- A. server1 only
- B. app1 only
- C. both server1 and local1
- D. both app1 and local1

Correct Answer: B

QUESTION 16

A TBO has been created for the custom object type called my_loan_application. If the following statement is executed in a Webtop custom component, where is the TBO executed?

```
IDfSysObject loanApp = (IDfSysObject)session.newObject("my_loan_application");
```

- A. The TBO executes on the client browser's JVM.
- B. The TBO executes on the Global Registry computer.

- C. The TBO executes on the application server JVM.
- D. The TBO executes on the Content Server JVM.

Correct Answer: C

QUESTION 17

How should you deploy a TBO to the repository?

- A. Using IDfClient.newModule() only
- B. Using Documentum Application Installer only
- C. Using both Documentum Application Installer and IDfClient.newModule()
- D. Using Documentum Application Installer, IDfClient.newModule() and IDfClient.newService()

Correct Answer: B

QUESTION 18

What are the minimum required components to extend custom object type behavior?

- A. TBO and SBO
- B. TBO and DFC
- C. SBO and DFC
- D. SBO and Web Services Framework

Correct Answer: B

QUESTION 19

A TBO has been created for a custom object type called my_loan_application. The TBO relies on a dependant SBO to calculate credit scores. The TBO is only invoked by the Webtop application. Where does the SBO execute?

- A. Global registry machine
- B. Content Server JVM
- C. Application Server JVM
- D. the client browser's JVM

Correct Answer: C

QUESTION 20

Given an SBO called com.mycompany.ICreditScore and the following statement:
newModule(repositoryName, "com.mycompany.ICreditScore", sessionMgr) What does the statement do?

- A. deploys com.mycompany.ICreditScore module
- B. deploys com.mycompany.ICreditScore service
- C. deploys and instantiates com.mycompany.ICreditScore module
- D. deploys and instantiates com.mycompany.ICreditScore service

Correct Answer: C

QUESTION 21

Which statement is true about Documentum Web Services Framework (WSF)?

- A. All business objects can be exposed as Services using WSF.
- B. Currently WSF does not support secured SOAP transfer.
- C. WSF does not require UDDI to discover Web services.
- D. Currently WSF only supports J2EE clients.

Correct Answer: C

QUESTION 22

Which statement is true about Connection Brokers?

- A. A Connection Broker is not required in order to establish a session between DFCAplication and Content Server.
- B. To perform IP translation through a firewall, you need to have two ConnectionBrokers.
- C. Load balancing across Connection Brokers is not natively supported.
- D. When you shut down a Content Server, it automatically shuts down its primaryConnection Broker.

Correct Answer: A

QUESTION 23

Given the following repositories that are projecting to the following Connection Brokers:
What is the output for the code, assuming you are using a session established to Docbase C from host2?

- A. null
- B. Docbase C
- C. Docbase B Docbase C
- D. Docbase A Docbase B Docbase C

Correct Answer: C

QUESTION 24

Which is NOT a valid interface?

- A. IDfCabinet
- B. IDfFolder
- C. IDfDocument
- D. IDfGroup

Correct Answer: A

QUESTION 25

Click the <Exhibit> button.

Which interface is missing in the diagram? ***Missing Exhibit***

- A. IDfFolder
- B. IDfCabinet
- C. IDfPersistentObject
- D. IDfNonPersistentObject

Correct Answer: C

QUESTION 26

How can you provide an interface for a custom object type that gets instantiated using DFC methods such as getObject()?

- A. extend IDfDocument
- B. extend IDfSysObject
- C. create a TBO with an interface for the custom object type
- D. create an SBO with an interface for the custom object type

Correct Answer: C

QUESTION 27

Which interface can be used when creating repository objects that have content?

- A. IDfTypedObject
- B. IDfDocument
- C. IDfPersistentObject
- D. IDfContentObject

Correct Answer: B

QUESTION 28

Which interface declares the save() method?

- A. IDfSysObject
- B. IDfTypedObject
- C. IDfDocument
- D. IDfPersistentObject

Correct Answer: D

QUESTION 29

A custom object type called my_loan_application is created with a custom repeating attribute called borrower_names. The data type of the attribute is String. Which interface declares a method to update borrower_names?

- A. IDfTypedObject
- B. IDfType
- C. IDfValueAssistance
- D. IDfCustomObject

Correct Answer: A

QUESTION 30

What is the correct hierarchy in the Documentum object model?

- A. dm_folder inherits from dm_cabinet, which inherits from dm_sysobject.
- B. dm_sysobject inherits from dm_document.
- C. dm_document inherits from dm_folder, which inherits from dm_sysobject.
- D. dm_category inherits from dm_folder, which inherits from dm_sysobject.

Correct Answer: D

QUESTION 31

Which statement is true about IDfClientX interface?

- A. It provides methods to add a Connection Broker to the list of brokers known to DFC.
- B. It provides methods to construct a session manager.
- C. It provides factory methods for operations.
- D. It provides methods to obtain an IDfTypedObject interface.

Correct Answer: C

QUESTION 32

Which is the correct DFC interface hierarchy?

- A. IDfSysObject extends IDfPersistentObject which extends IDfTypedObject.
- B. IDfSysObject extends IDfTypedObject which extends IDfPersistentObject.
- C. IDfFolder extends IDfCabinet which extends IDfSysobject.
- D. IDfPermit extends IDfACL which extends IDfSysobject.

Correct Answer: A

QUESTION 33

Which is a valid DFC package?

- A. com.documentum.da.user
- B. com.documentum.workflow
- C. com.documentum.transaction
- D. com.documentum.fc.lifecycle

Correct Answer: D

QUESTION 34

Which statement about non-persistent types is true?

- A. Non-persistent types can be referenced by r_object_id.
- B. Custom object types can inherit from non-persistent types.
- C. Non-persistent type attributes are stored in the repository.
- D. Non-persistent type attributes cannot be queried using DQL.

Correct Answer: D

QUESTION 35

Which interface does the IDfCollection interface inherit from?

- A. IDfTypedObject
- B. IDfSysObject
- C. IDfQuery
- D. IDfDocument

Correct Answer: A

QUESTION 36

When is a computed attribute calculated?

- A. once, when a session is opened
- B. each time the value is requested
- C. when a persistent object is saved
- D. when a persistent object is created

Correct Answer: B

QUESTION 37

Which specific object type in the repository does the IDfTypedObject interface represent?

- A. dm_dd_info
- B. dmi_dd_type_info
- C. dm_type
- D. none

Correct Answer: D

QUESTION 38

What entries do you need in the dmcl.ini for setting up dmcl tracing?

- A. trace_file and trace_level
- B. dmcl.trace.file and dmcl.trace.level

- C. tracing.enabled and tracing.level
- D. trace.file and trace.level

Correct Answer: A

QUESTION 39

What does the dfc.config.timeout entry in dfc.properties indicate?

- A. polling interval for changes in dfc.properties
- B. sleep interval for the DFC cleanup thread
- C. timeout for sessions in the DFC session pool
- D. polling interval for changes in log4j.properties

Correct Answer: A

QUESTION 40

DFC is NOT required to be installed on _____.

- A. the Content Server
- B. an Application Server hosting a WDK application
- C. an end user's computer using Webtop
- D. an end user's computer using Documentum Desktop

Correct Answer: C

QUESTION 41

Where is connection pooling set?

- A. dmcl.ini
- B. server.ini
- C. dfc.properties
- D. dbr.properties

Correct Answer: A

QUESTION 42

What are the minimum entries you need in the dfc.properties file to turn on tracing?

- A. dfc.tracing.enabled=true dfc.tracing.file=<file_path>
- B. dfc.tracing.enabled=true
- C. dfc.tracing.enabled=true dfc.tracing.file=<file_path> dfc.tracing.level=<level>
- D. dfc.tracing=true

Correct Answer: B

QUESTION 43

Which entry is mandatory for the dfc.properties file?

- A. dfc.data.dir
- B. dfc.user.dir
- C. dfc.checkout.dir
- D. dfc.registry.mode

Correct Answer: A

QUESTION 44

What do you need in dfc.properties to combine DFC and dmcl tracing?

- A. trace_file=<file_path> trace_level=<level>
- B. dfc.tracing.combineDMCL=true
- C. dfc.tracing.DMCL=true
- D. dmcl_trace_level=<level>

Correct Answer: B

QUESTION 45

During DFC installation, the "Primary Interop Assembly Installer checkbox" appears. What happens when this checkbox is checked?

- A. The DFC installation program executes the Microsoft installer package for the DFCPIA.
- B. The Microsoft installer package for the DFC PIA needs to be downloaded first, then the DFC installer will install the package for the DFC PIA.
- C. The DFC installation program places the Microsoft installer package for the DFC PIA into the setup subdirectory of the DFC program root directory.
- D. The DFC installation program does not install any package, but creates a Documentum user account and configures the database to make use of the PIA functionality.

Correct Answer: C

QUESTION 46

How can a client application adopt changes in the dmcl.ini settings regarding connection pooling?

- A. by restarting the client application, because open sessions cannot adopt connection pooling setting changes
- B. by restarting the repository in order to refresh the persistent cache
- C. by restarting the Connection Broker in order to reinitialize the session mapping and adopt the connection pooling changes
- D. by rebooting the Content Server, which will flush the server connections and reinitialize the global repository

Correct Answer: A

QUESTION 47

Which files are in the DFC config directory?

- A. dfc.jar, dctm.jar, workflow.jar, dfcbase.jar
- B. dfc.properties, log4j.properties, dfc.jar
- C. dfc.properties, log4j.properties, dfcfull.properties
- D. dfc.properties, log4j.properties, dfcfull.properties, dctm.properties

Correct Answer: C

QUESTION 48

An object type test_type extends dm_document, and has an attribute test_attr of type int. An object of type test_type exists in the repository with test_attr set to 1, and the object_id parameter in the following line of code points to that object.

```
IDfSysObject testObject = (IDfSysObject)session.getObject(object_id);
```

What happens as the result of calling testObject.getString("test_attr") ?

- A. null
- B. "1"
- C. ""
- D. an IDfException set to DM_DFC_E_TYPE_MISMATCH

Correct Answer: B

QUESTION 49

Given that document is an instance of an IDfDocument object, and given the following statement:

`document.setObjectName("test");` What will be the outcome?

- A. The code does NOT compile.
- B. At runtime, a `NoSuchMethodException` is thrown because `setObjectName()` is defined on `IDfSysObject`.
- C. At runtime, a `NoSuchMethodException` is thrown because `setObjectName()` is defined on `IDfPersistentObject`.
- D. The code runs successfully.

Correct Answer: D

QUESTION 50

Given the following code: Which statement is valid?

- A. `document.getPath()`
- B. `document.getType()`
- C. `document.getObjectId()`
- D. `document.getObjectName()`

Correct Answer: C

QUESTION 51

Which statements are required to create a new document object and link it to the Temp cabinet?

- A. `IDfDocument newDoc = (IDfDocument)session.newObject("dm_document");newDoc.link("/Temp");newDoc.save();`
- B. `IDfDocument newDoc = (IDfDocument)session.newObject("dm_document");newDoc.linkCabinet("/Temp");newDoc.save();`
- C. `IDfDocument newDoc = (IDfDocument)session.newObject("dm_document");newDoc.link(session.getFolderByPath("/Temp"));newDoc.save();`
- D. `IDfDocument newDoc = (IDfDocument)session.newObject("dm_document");newDoc.link(session.getIdByQualification("dm_cabinet where folder='/Temp'"));newDoc.save();`

Correct Answer: A

QUESTION 52

What does the `IDfPersistentObject` interface represent?

- A. only objects stored in the repository
- B. only objects NOT stored in the repository
- C. only objects with content stored in the repository
- D. only objects WITHOUT content stored in the repository

Correct Answer: A

QUESTION 53

What does the following statement do while updating a repeating attribute "attr_name" that has only one value in it (assuming valid objects and variables)?

`obj.setRepeatingString("attr_name", 2, "test");`

- A. updates `attr_name` with the value "test" at the third position

- B. throws a runtime DfException
- C. updates attr_name with the value "test" at the second position
- D. appends attr_name with the value "test"

Correct Answer: B

QUESTION 54

With an IDfSysObject representing a repository object named "MyDocument," which statement is valid and returns the object name?

- A. String value = object.getValue("object_name");
- B. String value = (String)object.getValue("object_name");
- C. String value = object.getValue("object_name").asString();
- D. String value = object.getValue("object_name").toString();

Correct Answer: C

QUESTION 55

attr_name is an attribute of type my_type, which is a subtype of dm_document. What do the following code statements do? (Assume you have valid variables and objects.)

- A. update attr_name with "test"
- B. throw a runtime DfException
- C. update attr_name with NULL
- D. NOT update attr_name

Correct Answer: A

QUESTION 56

What does the following code do?

- A. creates a new cabinet with the name specified by the variable "cabinetName"
- B. gives a runtime DfException of no link path
- C. gives a compilation error
- D. gives a runtime Class Cast Exception

Correct Answer: C

QUESTION 57

Which code statements would create a new folder (assuming valid objects and variables)?

- A. IDfFolder folder = (IDfFolder)session.newObject("dm_folder");folder.setFolderName(objectName);folder.link(filePath);folder.save();
- B. IDfFolder folder = (IDfFolder)session.newObject("dm_folder");folder.save();
- C. IDfFolder folder = (IDfFolder)session.newObject("dm_folder");folder.setObjectName(objectName);folder.link(filePath);
- D. IDfFolder folder = (IDfFolder)session.newObject("dm_folder");folder.setObjectName(objectName);folder.save();

Correct Answer: D

QUESTION 58

Given that attr_name is a single-valued attribute of type int with NO value set and assuming valid variables and objects, what would the following code do?

- A. throws a DfException
- B. returns the default value for int

- C. returns NULL
- D. returns a string of length 0

Correct Answer: B

QUESTION 59

What will the following method return when the object path contains multiple objects?

```
Public IDfPersistentObject getObjectByPath(Sting objectPath)
```

- A. all objects in the object path
- B. always the first object in the object path
- C. always the last object in the object path
- D. an object in the object path that cannot be determined

Correct Answer: D

QUESTION 60

Which is the valid method for retrieving the folder named "example1" located in the "dadmin" cabinet, given that the "dadmin" cabinet only contains one folder and that session is a valid IDfSession object?

- A. IDfFolder folder = session.getFolderByPath("example1");
- B. IDfFolder folder = session.getFolderByPath("/dadmin");
- C. IDfFolder folder = (IDfFolder)session.getObjectByPath("/dadmin");
- D. IDfFolder folder = session.getFolderByPath("/dadmin/example1");

Correct Answer: D

QUESTION 61

Given the following information about a document in the repository: If this is the only document in the cabinet shown, which statement will have the best performance when querying for the object?

- A. IDfPersistentObject obj = session.getObject(clientX.getId("094af3ce80000200"));
- B. IDfId id = session.getIdByQualification("where r_object_id='094af3ce80000200'");
- C. IDfPersistentObject obj = session.getObjectByPath("/Marketing/logo.jpg");
- D. IDfPersistentObject obj = session.getObjectByQualification("where r_folder_path='/Marketing' and object_name='logo.jpg'");

Correct Answer: A

QUESTION 62

Which version of a document, given a valid ID, is certain to be returned when the following method is called? IDfSession.getObject(IDfId objectId)

- A. first version
- B. last version
- C. current version
- D. specific version

Correct Answer: D

QUESTION 63

In which interface is the following method declared? public IDfPersistentObject getObjectByQualification (String qualification)

- A. IDfQuery
- B. IDfSession
- C. IDfSysObject

D. IDfPersistentObject

Correct Answer: B

QUESTION 64

You want to retrieve one document from a specific cabinet 'XYZ' using the getObjectByQualification(String qualification) method. Which qualifier should you use?

- A. dm_document WHERE FOLDER('/XYZ')
- B. dm_document WHERE r_folder_path = '/XYZ'
- C. SELECT r_object_id FROM dm_document WHERE FOLDER('/XYZ')
- D. SELECT r_object_id FROM dm_document WHERE r_folder_path = '/XYZ'

Correct Answer: A

QUESTION 65

Given the following steps: Which statement is true?

- A. The object cannot be deleted in Step 3.
- B. getObject method will always raise an exception.
- C. getObject method may succeed since the object may be present in the client and/or servercache.
- D. getObject method will return null.

Correct Answer: C

QUESTION 66

What does the object retrieval method getObjectByQualification() do if the provided query returns no object?

- A. throws a DfObjectNotFoundException
- B. returns null.
- C. returns an IDfCollection object containing no element
- D. throws a DfResultContentException

Correct Answer: B

QUESTION 67

You want to get an object, but there is more than one object that meets the qualification. What should you do?

- A. iterate through the results of the getFolderByPath() method
- B. use the getObjectByQualification() method with a qualifier that includes all of the objects
- C. use a query and iterate through the resulting collection
- D. use the getObjectPaths() and iterate through the resulting enumeration

Correct Answer: C

QUESTION 68

Which statement is used to retrieve the current version of a dm_document object that has 2 versions, given its chronicle id chronicle_id?

- A. getObject(chronicle_id)
- B. getObjectByQualification("dm_document (all) where r_object_id = " + chronicle_id + """)
- C. getObjectByQualification("dm_document where i_chronicle_id = " + chronicle_id + """)
- D. getObjectByQualification("select r_object_id from dm_document (all) where i_chronicle_id = " + chronicle_id + """)

Correct Answer: C

QUESTION 69

What is the result of executing the following code? (Assume that all variables and constants are valid.)

- A. no records
- B. all dm_document objects in the repository
- C. current versions of all dm_document objects in the repository
- D. An exception is thrown as no attributes have been specified in the select clause.

Correct Answer: C

QUESTION 70

Which method properly executes a query and returns the appropriate results. Assume you are developing a UI tree control in a web application to display a list of cabinets. The list of cabinets is generally static. Given the below code snippet: Which value for queryType should be used to achieve the maximum performance?

- A. IDfQuery.DF_READ_QUERY
- B. IDfQuery.DF_QUERY
- C. IDfQuery.DF_CACHE_QUERY
- D. IDfQuery.DF_EXECCREAD_QUERY

Correct Answer: C

QUESTION 71

Given the following code: How would you limit the search to the Temp cabinet?

- A. Add IDfExpressionSet expSet = qBuilder.getRootExpressionSet();expSet.addSimpleAttrExpression("object_name", IDfValue.DF_STRING, IDfSimpleAttrExpression.SEARCH_OP_EQUAL, false, false, "Temp");
- B. Add qBuilder.setDQL("Folder('/Temp')");
- C. Add qBuilder.addLocationScope("Repository", "/Temp", false);
- D. This cannot be done in the IDfQueryManager.

Correct Answer: C

QUESTION 72

Assuming that repository "A" has 100 dm_document objects with the name "test" in the object_name, how many records would be returned when the code below is executed?

- A. 0
- B. 99
- C. 100
- D. 101

Correct Answer: A

QUESTION 73

How many objects will have their subject attribute updated when the following code is executed? (Assume that there are 25 objects having the string 'test' in their object_name.)

- A. 19
- B. 20
- C. 24
- D. 25

Correct Answer: B

QUESTION 74

Which statement is true using fetch rather than a query to return attributes?

- A. use fetch when you need to retrieve all attributes of an object
- B. use fetch when you need to retrieve only specific attributes of an object
- C. use query when attribute information is repeatedly needed in multiple places
- D. use query when caching is necessary on the client side

Correct Answer: A

QUESTION 75

The IDfQuery interface provides _____.

- A. status information about the execution of a query
- B. a container for passing a query string directly to the search source
- C. factory methods for a query and interfaces for persistent query management
- D. functionality to set how often the query results need to be checked for consistency with the server

Correct Answer: A

QUESTION 76

Which statement is true about query types?

- A. DF_CACHE_QUERY is used for long query strings and stores results in a query cache file.
- B. DF_EXEC_QUERY is used for long query strings that will not affect any repository data during processing.
- C. DF_QUERY can be used for any DQL Query and generally used for any query that will affect the repository.
- D. DF_EXECCREAD_QUERY is used for long query strings that will affect any repository data during processing.

Correct Answer: C

QUESTION 77

What does the IDfCollection.getTypedObject() method return?

- A. all rows in the collection as a single object for later use
- B. a row in the collection for later use
- C. a row in the collection that must be used before the collection is closed
- D. an object of type IDfTypedObject that can be cast to an IDfPersistentObject

Correct Answer: B

QUESTION 78

Given the following: where queryString = "select object_name from dm_document" Which method properly executes a query and returns the appropriate results?

- A. `public static IDfCollection execQuery(String queryString, IDfSession session) throws DfException{...`
- B. `setDQL(queryString);col = q.execute(session);...return col;`
- C. `public static IDfCollection execQuery(String queryString, IDfSession session) throws DfException{...`
- D. `setDQL(queryString);col = q.execute(session,0);...return col;`
- E. `public static IDfDocument execQuery(String queryString, IDfSession session) throws DfException{...`
- F. `setDQL(queryString);objectName = q.execute(session);...return objectName;`
- G. `public static IDfDocument execQuery(String queryString, IDfSession session)`


```
throwsDfException{...
```

```
H. setDQL(queryString);objectName = q.execute(session,0);...return objectName;}
```

Correct Answer: B

QUESTION 79

Which statement is NOT true about IDfOperationMonitor?

- A. It allows applications to be notified about when an error occurs.
- B. It allows applications to receive progress about the percentage complete for the whole operation.
- C. It allows applications to be notified and respond with an answer when an error occurs.
- D. It allows applications to receive progress about the bytes transferred during a content upload or download.

Correct Answer: D

QUESTION 80

Which interface provides the factory methods for creating DFC operations such as IDfImportOperation and IDfExportOperation?

- A. IDfClientX
- B. IDfSysObject
- C. IDfSession
- D. IDfSessionMgr

Correct Answer: A

QUESTION 81

What happens when the abort() method is executed in the following manner? (Assume the operation is populated.)

- A. This code will cause an error as the operation has already been executed.
- B. Abort can only be called from within an IDfOperationMonitor object.
- C. The underlying database transaction will be rolled back.
- D. The operation will attempt to undo what it did during the execution.

Correct Answer: D

QUESTION 82

Given the following statement for creating a IDfCheckinNode object:

```
IDfCheckinNode node = (IDfCheckinNode)checkin.add( doc);
```

Which statement should immediately follow?

- A. if (node == null) { /* handle errors */ }
- B. node.setFilePath(strFileName);
- C. checkin.execute();
- D. node.setVersionLabels("DRAFT");

Correct Answer: A

QUESTION 83

You are using the IDfMoveOperation to move a document that is currently checked out. What is the behavior of DFC?

- A. It moves the document and the lock is still present on the document.
- B. IDfMoveOperation.execute() method returns false and the document location is unchanged.

- C. IDfMoveOperation.add() method throws a DfException since checked-out objects cannot be added to a move operation.
- D. It reports an error (IDfOperationError.OBJECT_CHECKED_OUT) using the operation monitor and gives the option to still move the document.

Correct Answer: B

QUESTION 84

Given the following code (Assume the variables are valid.):

What is the required statement to include, in order for the code to execute successfully?

- A. node.setDestinationFolderId(destnId);
- B. op.setSession(session);
- C. op.setOperationMonitor(myOpMonitor);
- D. node.setDocbaseObjectType("dm_document");

Correct Answer: B

QUESTION 85

Which code pattern is used to handle errors after execution of an operation?

- A. IDfOperationMonitor myOpMonitor = ...; operation.setOperationMonitor(myOpMonitor); if (! operation.execute()) { // handle errors using myOpMonitor }
- B. if (! operation.execute()) { ... operation.reportError(...); ... }
- C. if (! operation.execute()) { ... operation.logError(...); ... }
- D. if (! operation.execute()) { ... operation.getErrors(); ... }

Correct Answer: D

QUESTION 86

You have a handle to an IDfVirtualDocument using the following code: Which steps are the recommended way to only add the root node of a virtual document to the operation (i.e. in the call operation.add(...))?

- A. 1. Execute the statement: operation.add(vDoc); 2. Do nothing since DFC always adds the virtual document root only. If children are needed as well, they must be explicitly added by traversing the virtual document.
- B. 1. Execute the statement: operation.add(vDoc); 2. Remove the child nodes explicitly from the root node (node.removeChildren()) since DFC added them automatically.
- C. 1. Execute the statement: operation.add(sysObject); 2. Do nothing since there is no difference between adding a regular sys object and just the virtual document root.
- D. 1. Remove the child nodes from vDoc in memory (i.e. not saving to repository) and then call 2. Execute the statement: operation.add(vDoc);

Correct Answer: C

QUESTION 87

What happens when the following code for deleting a document is executed?

- A. All versions of the document will be deleted.
- B. Only the specific version associated with the document in question will be deleted.
- C. Only the specific version associated with the document in question and all prior versions will be deleted.
- D. The document will not be deleted since the version deletion policy has not been explicitly set using the op.setVersionDeletionPolicy() call.

Correct Answer: B

QUESTION 88

The transform operation in the com.documentum.operations package allows you to transform _____.

- A. any kind of content from one format to another and the transformed content is only available locally
- B. any kind of content from one format to another and the transformed content is only available as a rendition in the repository
- C. any kind of content to PDF and the transformed content is available locally or as a PDF rendition in the repository
- D. only XML content using XSLT and the transformed content is available locally or in the repository

Correct Answer: D

QUESTION 89

What is the default behavior when you add a directory from the file system to an import operation?

- A. The directory will be imported by itself.
- B. The directory and all documents it contains will be imported.
- C. The directory and all files and subdirectories will be imported.
- D. It will result in an error.

Correct Answer: C

QUESTION 90

Which statement about Operations is true?

- A. Operations can be used to Cancel Checkout.
- B. Operations can be used to Add Rendition.
- C. Operations can be used to Promote.
- D. Operations can be used to Assign Workflow.

Correct Answer: A

QUESTION 91

The IDfValidationOperation interface is used to validate _____.

- A. that objects conform to the data dictionary rules
- B. that objects are not corrupt in the repository
- C. any office documents, making sure that all their OLE links are valid
- D. that XML documents are well formed and conform to a DTD or schema

Correct Answer: D

QUESTION 92

What does the IDfSysObject.checkout() method do?

- A. only places a lock on an object from the repository
- B. places a lock on an object from the repository and downloads the content
- C. places a database row level lock on the rows representing the object
- D. places a lock on an object from the repository and sets its r_lock_machine attribute

Correct Answer: D

QUESTION 93

When is it appropriate to use IDfSysObject.getFile(String fileName) ?

- A. to get a file from the file system for an object
- B. to get the file to a specific location on the client machine with the default format
- C. to get a file and manipulate it in memory
- D. to get a specific page of the object and download it to the default location on the client machine with the

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Trying our product !



- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

[Guarantee & Policy](#) | [Privacy & Policy](#) | [Terms & Conditions](#)

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2015, All Rights Reserved.