

100% Money Back
Guarantee

Vendor: SolarWinds

Exam Code: SCP-500

Exam Name: SolarWinds Certified Professional

Version: Demo

QUESTION 1

The data center team requires that they be alerted if any of the servers in a remote site go down. However, they do NOT want to receive alerts when the remote site connection goes down. Which two configuration steps should you take within your network management system (NMS) to meet these requirements? (Choose two.)

- A. set up alerts on server status
- B. set up alerts on the remote connection status
- C. set each of the servers as dependencies for each other
- D. set up the remote connection as a dependency for each of the servers
- E. set up alerts on the remote router status

Correct Answer: AD

QUESTION 2

What is an advantage of using SNMPv2c over using SNMPv1?

- A. username parameter
- B. get bulk command
- C. get next command
- D. 32 bit counters
- E. authentication and encryption

Correct Answer: B

QUESTION 3

Which two variables are used in the calculation of Percent Utilization? (Choose two.)

- A. configured bandwidth
- B. packets per second
- C. buffer overruns
- D. interface discards
- E. bits per second

Correct Answer: AE

QUESTION 4

Due to a server crash, you had to move Orion to a new server with a new IP address. Which two changes should you make to ensure that Orion functions properly from the new server and IP address? (Choose two.)

- A. update the access control lists (ACLs) that restrict management protocols
- B. change the IP address specified in the snmpd.conf file on the Orion server
- C. updates the source address for Net Flow packets exported to Orion
- D. notify ARIN of the Orion server's new IP address
- E. update the destination IP address for Syslog and SNMP traps on your managed devices

Correct Answer: AE

QUESTION 5

You are monitoring your Internet connection, and your ISP has guaranteed 512 Kbps. Historical data shows that your connection speed holds at 256 Kbps for long periods of time, but never exceeds this speed. What does this indicate?

- A. the ISP has misconfigured the link.
- B. the WAN router is misconfigured.

- C. the NAT table is overloaded.
- D. QoS is dropping low priority traffic.

Correct Answer: A

QUESTION 6

Your current deployment has multiple Orion NPM servers monitoring multiple locations from a single site. This is producing inaccurate data and high WAN bandwidth utilization. What are the two most efficient ways to address this issue? (Choose two.)

- A. deploy Orion NPMat each remote location
- B. deploy Orion Enterprise Operations Console
- C. deploy an additional Orion Poller
- D. deploy an additional Orion Web Server
- E. deploy an Orion Hot Standby

Correct Answer: AB

QUESTION 7

How does the Orion Universal Device Poller (UnDP) monitor a device's statistics that are Not included in the standard Orion NPM MIB database?

- A. by manually associating the device'sOID to Orion
- B. by keeping a copy of the device's MIB on the Orion NPM Server
- C. by automatically searching the common MIB repositories and updating Orion
- D. by manually compiling the MIB into the Orion MIB database
- E. by manually compiling the OID into the Orion MIB database

Correct Answer: A

QUESTION 8

Which protocol should a network engineer enable on routers and switches to collect utilization statistics?

- A. ICMP
- B. SNMP
- C. SMTP
- D. WMI

Correct Answer: B

QUESTION 9

A network engineer is enabling SNMP on their network devices and needs to ensure it will use message integrity. Which version of SNMP should they use?

- A. SNMPv1
- B. SNMPv2c
- C. SNMPv3
- D. SNMPv4

Correct Answer: C

QUESTION 10

A network engineer notices the Syslog server's database is growing significantly in size due to the large number of devices sending Syslog messages. What should the engineer do to control database growth?

- A. configure the Syslog server to discard unwanted messages
- B. configure the devices and the Syslog server to use TCP-based Syslog

- C. configure the devices and the Syslog server to use SNMPv3
- D. configure the Syslog server to capture SNMP traps instead of Syslog

Correct Answer: A

QUESTION 11

You have recently implemented a VoIP infrastructure within the company network. You are receiving trouble tickets indicating calls are dropping between their New York and San Francisco offices. Which two IP service level agreement (SLA) measurements should you use to identify the cause of the issue?

- A. latency
- B. SIP
- C. NetFlow
- D. available bandwidth
- E. jitter

Correct Answer: AE

QUESTION 12

Which two performance metrics can be affected by proper QoS implementation? (Choose two.)

- A. jitter
- B. shaping
- C. marking
- D. queuing
- E. latency

Correct Answer: AE

QUESTION 13

Which network protocols are used by Solar Winds products during network discoveries?

- A. ICMP and SMTP
- B. DHCP and TFTP
- C. PPTP and IMAP
- D. ICMP and SNMP

Correct Answer: D

QUESTION 14

Which two management protocols should you use to measure the effectiveness of your QoS implementation? (Choose two.)

- A. Syslog
- B. SNMP
- C. NetFlow
- D. WMI
- E. SSHv2

Correct Answer: BC

QUESTION 15

Which management protocol should you use to analyze network traffic in and out of a router interface?

- A. WMI
- B. Syslog
- C. IP service level agreement (SLA)

D. sFlow

Correct Answer: D

QUESTION 16

Users are complaining that a network connection is slow. How should SNMP be used to verify performance of the interface?

- A. verify bandwidth usage via if InOctets
- B. verify status via the if Table
- C. verify that SNMP agent is responding
- D. verify the performance via if Speed

Correct Answer: A

QUESTION 17

Orion NPM is monitoring the performance of DS-3 utilizing standard MIBs in the ifTable. Occasionally, the reported traffic rates for this interface spike well above 45 Mbps. What is the most likely cause?

- A. heavy network traffic
- B. carrier misconfiguration
- C. counter rollovers
- D. database issues

Correct Answer: C

QUESTION 18

Orion NPM is using SNMP to poll a router and track interface traffic rates. The data are collected every 5 minutes, and the most recent values collected for a specific interface are 1,000,000 and 2,000,000 octets. What is the approximate average rate of traffic for this interface?

- A. 1 Kbps
- B. 3 Kbps
- C. 16 Kbps
- D. 26 Kbps

Correct Answer: D

QUESTION 19

When using a network management system (NMS) to monitor network interfaces on a router, you notice that statistics are wrong after an interface card is physically removed from the device. What has most likely caused this problem?

- A. interface re-indexing
- B. device configuration
- C. counter rollovers
- D. access lists

Correct Answer: A

QUESTION 20

Which two reporting requirements should you consider when specifying data roll-up settings for a network management system (NMS)? (Choose two.)

- A. data encryption
- B. data format
- C. data granularity
- D. monitoring coverage

E. data retention

Correct Answer: CE

QUESTION 21

Which advantage do SNMP traps and Syslog have over SNMP polling?

- A. reliability of event detection
- B. ability to poll events in real-time
- C. ease of configuration
- D. speed of event detection

Correct Answer: D

QUESTION 22

How can you use a network management system (NMS) to ensure service level agreement (SLA) parameters are realistic for your environment?

- A. increase data collection period
- B. configuredata summarization
- C. reducedata retention period
- D. baseline network performance

Correct Answer: D

QUESTION 23

Your service level agreement (SLA) dictates that you must be able to notify the appropriate parties when systems are down for over2 minutes and report on data for the last120 days. Your network management system (NMS) has been configured to collect status every 10minutes and summarizes and retains data for 90 days. Which two settings should you change in the NMS to meet the business requirements? (Choose two.)

- A. increase data retention to 120 days
- B. configure status polling to occur every5 minutes
- C. summarize hourly data into weekly data every 120 days
- D. configure status polling to occur every minute
- E. summarize hourly data into weekly data every 90 days

Correct Answer: AD

QUESTION 24

What should you do to track whether a new configuration has alleviated slow network performance?

- A. compare ICMP availability before and after the change
- B. compare application responsiveness before and after the change
- C. monitor the affected devices for stability
- D. monitor bandwidth utilization on affected interfaces

Correct Answer: B

QUESTION 25

The IT budgeting department has asked you for reports that will help them better plan for increases in monthly recurring costs. Which report should you set up to help the IT udgeting department meet this objective?

- A. router inventory
- B. WAN interface utilization
- C. LAN interface utilization

D. available switch ports

Correct Answer: B

QUESTION 26

IT management wants to know how they can lower their total power consumption by consolidating equipment and shutting off unnecessary equipment. Which type of report can you create to help them plan for this?

- A. bandwidth utilization
- B. available switch ports
- C. router CPU utilization
- D. total NetFlow endpoints

Correct Answer: B

QUESTION 27

The IT planning department has asked for a report to help them understand when they need to implement IPv6. Which report would offer them the greatest amount of relevant information?

- A. unique NetFlow exporters
- B. DHCP server CPU utilization
- C. number of subnets
- D. IP address utilization trends

Correct Answer: D

QUESTION 28

You are planning a network management implementation where the network has several low bandwidth WAN links. Which two network management protocols are most likely to cause heavy traffic on WANs and should therefore be considered carefully before deployment? (Choose two.)

- A. Syslog
- B. SSH
- C. SMTP
- D. NetFlow
- E. ICMP

Correct Answer: AD

QUESTION 29

Which two sources provide detailed visibility into router interface traffic? (Choose two.)

- A. SNMP statistics
- B. SNMP traps
- C. NetFlow
- D. Syslog
- E. CDP

Correct Answer: AC

QUESTION 30

A network engineer is planning to deploy a network management system (NMS) to monitor a network. Which two UDP ports should be enabled in router access control lists and firewalls so the NMS can effectively monitor devices? (Choose two.)

- A. 160
- B. 161

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



| | | |
|---|---|--|
|  One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p> |  Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p> |  Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p> |
|---|---|--|

[Guarantee & Policy](#) | [Privacy & Policy](#) | [Terms & Conditions](#)

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2015, All Rights Reserved.